


Z960Y/Z962Y型高温高压电站闸阀



select	Inquiry	型 号Type	公称通 径DN(mm)	L	尺寸Dimension(mm)					重 量Weight(kg)
					D1	D2	D3	T1	T2	
Z960Y-200 Z962Y-200	80	406	74	89	114	15	12	564	140	
Z960Y-200 Z962Y-200	100	483	97	115	144	16	15	580	187	
Z960Y-200 Z962Y-200	125	559	122	142	177	18	16	625	236	
Z960Y-200 Z962Y-200	150	635	146	168	212	20	17	1052	294	
Z960Y-200 Z962Y-200	175	711	184	219	238	24	22	1101	439	
Z960Y-200 Z962Y-200	200	788	194	219	277	24	22	1101	439	
Z960Y-200 Z962Y-200	225	864	194	273	300	28	26	976	878	
Z960Y-200 Z962Y-200	250	911	243	273	344	28	26	1078	878	
Z960Y-200 Z962Y-200	275	1067	243	324	574	32	30	1182	1280	
Z960Y-200 Z962Y-200	300	1194	289	324	402	32	30	1240	1280	
Z960Y-200 Z962Y-200	350	1560	318	356	466	34	32	1364	1710	
Z960Y-250 Z962Y-250	80	406	74	89	114	15	12	564	140	
Z960Y-250 Z962Y-250	100	483	97	115	144	16	15	580	187	
Z960Y-250 Z962Y-250	125	559	122	142	177	18	16	625	236	
Z960Y-250 Z962Y-250	150	635	146	168	212	20	17	1052	294	

Z960Y/Z962Y型高温高压电站闸阀

Z960Y-250 Z962Y-250	175	711	184	219	238	24	22	1101	439
Z960Y-250 Z962Y-250	200	788	194	219	277	24	22	1101	439
Z960Y-250 Z962Y-250	225	864	194	273	300	28	26	976	878
Z960Y-250 Z962Y-250	250	911	243	273	344	28	26	1078	878
Z960Y-250 Z962Y-250	275	1067	243	324	574	32	30	1182	1280
Z960Y-250 Z962Y-250	300	1194	289	324	402	32	30	1240	1280
Z960Y-250 Z962Y-250	350	1560	318	356	466	34	32	1364	1710
Z960Y-320 Z962Y-320	80	458	67	89	121	20	19	940	195
Z960Y-320 Z962Y-320	100	533	92	115	160	20	19	1095	331
Z960Y-320 Z962Y-320	125	610	116	142	172	24	22	1325	454
Z960Y-320 Z962Y-320	175	762	140	219	244	35	31	1500	1131
Z960Y-320 Z962Y-320	225	914	183	273	323	38	36	1518	1406
Z960Y-320 Z962Y-320	250	1041	283	273	323	45	43	1536	1725
Z960Y-320 Z962Y-320	275	1080	273	324	427	50	47	1763	1831
Z960Y-P54100 Z962Y-P54100	80	458	67	89	121	20	19	940	195